



5332 Dansher Road
Countryside, Illinois 60525

MATERIAL SAFETY DATA SHEET

Revision Date: 2/28/2008

MSDS No. GS-506

Emergency Phones: 708-579-8100

800-424-9300 (CHEMTREC)

PLEASE NOTE: This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this material. Please read the information on these sheets, and then provide this information to those people at your company whose responsibility it is to comply with FEDERAL and STATE RIGHT-TO-KNOW regulations. Also make this information available to any employee who requests it. It is your obligation to comply with these regulations.

SECTION I - PRODUCT IDENTITY

PRODUCT NAME: e.Mulsify Floor Stripper

Formula: Mixture, butyl cellosolve, amine, builders and detergents in water

Chemical Type: As above

HMIS RATINGS

Health = 2 (Moderate)	Flammability = 0 (Minimal)
Reactivity = 0 (Minimal)	Protection = B (Goggles, Gloves)

SECTION II - HAZARDOUS INGREDIENTS

	<u>PERCENT</u>	<u>TLV</u>	<u>CARCINOGEN (OSHA,TP,IARC)</u>
Ethanolamine (mono) CAS No. 141-43-5	0-2.5%	3 ppm	No
EG Phenyl Ether CAS No. 122-99-6	2.5-10%		No
Na Octanesulfonate CAS No. 5324-84-5	2.5-10%		No
PG n-Butyl Ether CAS No. 5131-66-8	1-5%		No

SECTION III - CHEMICAL AND PHYSICAL

Appearance: Clear Liquid	Boiling Point: 212° F.
Odor: Mild Sweet Solvent	Melting Point: N/A
Ph: N/A	Spec. Gravity (H ₂ O = 1): 1.025
Water Solubility: Complete	Vapor Pressure (Mm Hg): N/A
Viscosity: Water Thin	

SECTION IV - FIRE AND EXPLOSION HAZARDS

Flash Point (Method): >140°F Cl.cp.	Explosion Limits:	Upper: N/A
		Lower: N/A

Extinguishing Media: Water fog, CO₂, halon system, foam

Special Firefighting Procedures and Hazards Avoid skin and eye contact, and breathing of vapors. Wear head and body protection and alkali respirator if exposure to liquid is likely.

SECTION V - REACTIVITY INFORMATION

Stable: Unstable:

Precautions:

Incompatibility: Strong acids and materials not resistant to alkalis, active metals (zinc, aluminum, magnesium, etc.)

Hazardous Decomposition Products: Contact with active metals can release flammable hydrogen gas. If in a fire CO, CO₂ and hydrocarbons.

Hazardous Polymerization: Occurs:

Does Not Occur:

SECTION VI - HEALTH HAZARDS - PROTECTIVE MEASURES - FIRST AID

Inhalation: Breathing of mists causes respiratory irritation and can cause burns. Wear approved alkali mist respirator if exposure is likely. This is suggestion in an area of no ventilation. Remove to fresh air. Get medical attention if needed.

Skin: Flush skin with water for 15 minutes. Wear protective gloves. Get medical attention for any irritation.

Eyes: Wear goggles. Flush immediately with water for 15 minutes. Get prompt medical attention if needed.

Ingestion: Causes irritation or possible burns in mouth and throat and a mild gastric disturbance. Also may result in the absorption of potentially harmful amounts leading to possible liver and kidney damage. Rinse mouth. Drink lot of water or, preferably milk or juices. Do not induce vomiting. Get medical attention if effects persist.

Most likely routes of entry: Skin, Eyes.

Other Important Medical or Precautionary Information: None

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Spills and Leaks: Small spills can be flushed into normal drainage or into ground with copious amounts of water, or taken up with absorbent material. Do not drain to sewer without dilution. Larger spills should be contained by diking or other methods and held for disposal or reuse.

Storage and Handling: Check daily for any leaks from containers, vessels, pumps, and piping. Have water hoses and acid convenient. Use only containers and equipment designed for alkali services.

Waste Disposal: Product may be disposable in sewers if neutralized and if local regulations permit. Otherwise send to a licensed treatment facility.

Empty Containers: Rinse well before handling and disposal. Observe label precautions.

Other Precautions: In an enclosed area ventilate in any suitable manner.

SECTION VIII - REGULATORY INFORMATION

Reportable for SARA Title III, S.313 (Form R): 2-Butoxyethanol

The information herein has been compiled from sources believed to be reliable and is accurate to the best of our knowledge. However, ChemBlend International cannot give any guarantees regarding information from other sources, and expressly does not make any warranties, nor assumes any liability, for its use.